



MMX-4I-UH

The MMX-4I-UH is an HDMI 4K input card with audio embedded signal for MMX system.

| | |
|-------------------|--|
| Port | 4 x HDMI (Female HDMI) T.M.D.S 2.9V ~ 3.3V; 4 x Stereo audio (captive screw connector); 4 x RS232 (Captive screw connector) |
| Signal Standard | HDMI 1.4 & HDCP Compliant |
| EDID | Supports EDID Management |
| Audio Format | Embedded HDMI audio: PCM |
| Work Temperature | 0 ~ +50°C |
| Relative Humidity | 10% ~ 90% |



MMX-4I-BT

The MMX-4I-BT is an HDBaseT 4K input card with audio embedded signal for MMX system.

| | |
|-----------------------|--|
| Port | 4 x HDBT (Female RJ45) 4 x Stereo audio (captive screw connector); 4 x RS232 (Captive screw connector) |
| Signal Standard | HDMI 1.4 & HDCP Compliant |
| Bandwidth | 10.2Gbps |
| Transmission Distance | 1080P≤70m 4Kx2K ≤ 40m |
| EDID | Supports EDID Management |
| Audio Format | Embedded HDMI audio: PCM |
| Work Temperature | 0 ~ +50°C |
| Relative Humidity | 10% ~ 90% |



MMX-4I-UF

The MMX-4I-UF is an Optical fiber 4K input card for MMX system. It support single-mode and multi-mode optical fiber.

| | |
|-----------------------|---|
| Port | 4 x Fiber Optical (SPF Fiber Optical Connector) |
| Fiber Type | Single-Mode & Multi-Mode |
| Bandwidth | 10.2 Gbps |
| Color depth | 8bit, 10bit, 12bit, 16bit |
| Connector | LC connector |
| Resolution | Up to 4Kx2K |
| Transmission Distance | 300m (OM3 Multi-Mode Fiber) / 1km Single-Mode Fiber for 4K |
| Work Temperature | 0 ~ +50°C |
| Relative Humidity | 10% ~ 90% |

MMX 4K Input Cards